

Soil And Waste Discharge Pipes ,Orange, Single Solvent Socket ,Push Fit , 6m



Standard :EN 1401-1

Code No .	Thickness (mm)	Nominal Outside Diameter (mm)	Application Area Code	Ring Stiffness
PG 1942 P	3.2	110	UD	SN4 , SN8
PG 1947 P	4.2	110	UD	SN16
PG 2482 P	3.2	125	UD	SN4
PG 2483 P	3.7	125	UD	SN8
PG 2488 P	4.8	125	UD	SN16
PG 3191 P	3.2	160	U	SN2
PG 3192 P	4.0	160	UD	SN4
PG 3194 P	4.7	160	UD	SN8
PG 3200 P	6.2	160	UD	SN16
PG 3767 P	4.0	200	U	SN2
PG 3768 P	4.9	200	UD	SN4

Code No .	Thickness (mm)	Nominal Outside Diameter (mm)	Application Area Code	Ring Stiffness
PG 3770 P	5.9	200	UD	SN8
PG 3775 P	7.7	200	UD	SN16
PG 4620 P	4.9	250	U	SN2
PG 4621 P	6.2	250	UD	SN4
PG 4623 P	7.3	250	UD	SN8
PG 4628 P	9.6	250	UD	SN16
PG 5500 P	6.2	315	U	SN2
PG 5501 P	7.7	315	UD	SN4
PG 5502 P	9.2	315	UD	SN8
PG 5509 P	12.1	315	UD	SN16
PG 5985 P	7.0	355	U	SN2
PG 5986 P	8.7	355	UD	SN4
PG 5987 P	10.4	355	UD	SN8
PG 5994 P	13.6	355	UD	SN16
PG 6500 P	7.9	400	U	SN2
PG 6501 P	9.8	400	UD	SN4
PG 6503 P	11.7	400	UD	SN8
PG 6509 P	15.3	400	UD	SN16
PG 7103 P	11.0	450	UD	SN4
PG 7105 P	13.2	450	UD	SN8
PG 7108 P	17.2	450	UD	SN16
PG 7700 P	9.8	500	U	SN2
PG 7701 P	12.3	500	UD	SN4
PG 7703 P	14.6	500	UD	SN8

Code No .	Thickness (mm)	Nominal Outside Diameter (mm)	Application Area Code	Ring Stiffness
PG 7709 P	19.1	500	UD	SN16
PG 8300 P	12.3	630	U	SN2
PG 8301 P	15.4	630	UD	SN4
PG 8303 P	18.4	630	UD	SN8
PG 8307 P	24.1	630	UD	SN16

PG