

Threaded Well Casing Pipes Without Perforation Blue*



Standard :DIN 4925

Code No	Length (L)	Thickness (s)	Outside Diameter (d)	Nominal Diameter (DN)	Thread Type	Weight (kg)
PG 10121 P	1	5	113	100	Tr	2.750
PG 10122 P	2	5	113	100	Tr	5.145
PG 10123 P	3	5	113	100	Tr	7.543
PG 10124 P	4	5	113	100	Tr	9.943
PG 10187 P	1	7	113	100	Tr	3.740
PG 10188 P	2	7	113	100	Tr	7.035
PG 10189 P	3	7	113	100	Tr	10.333
PG 10190 P	4	7	113	100	Tr	13.633
PG 10253 P	1	6.5	140	125	Tr	4.400
PG 10254 P	2	6.5	140	125	Tr	8.400
PG 10255 P	3	6.5	140	125	Tr	12.400

Code No	Length (L)	Thickness (s)	Outside Diameter (d)	Nominal Diameter (DN)	Thread Type	Weight (kg)
PG 10256 P	4	6.5	140	125	Tr	16.400
PG 10319 P	1	8	140	125	Tr	5.335
PG 10320 P	2	8	140	125	Tr	10.185
PG 10321 P	3	8	140	125	Tr	15.035
PG 10322 P	4	8	140	125	Tr	19.885
PG 10385 P	1	7.5	165	150	Tr	5.995
PG 10386 P	2	7.5	165	150	Tr	11.445
PG 10387 P	3	7.5	165	150	Tr	16.895
PG 10388 P	4	7.5	165	150	Tr	22.345
PG 10451 P	1	9.5	165	150	Tr	7.480
PG 10452 P	2	9.5	165	150	Tr	14.280
PG 10453 P	3	9.5	165	150	Tr	21.080
PG 10454 P	4	9.5	165	150	Tr	27.880
PG 10517 P	1	10	225	200	Tr	10.835
PG 10518 P	2	10	225	200	Tr	20.685
PG 10519 P	3	10	225	200	Tr	30.587
PG 10520 P	4	10	225	200	Tr	40.488
PG 10583 P	1	13	225	200	Tr	13.915
PG 10584 P	2	13	225	200	Tr	26.565
PG 10585 P	3	13	225	200	Tr	39.267
PG 10586 P	4	13	225	200	Tr	51.763
PG 10649 P	1	12.5	280	250	Tr	16.830
PG 10650 P	2	12.5	280	250	Tr	32.130

Code No	Length (L)	Thickness (s)	Outside Diameter (d)	Nominal Diameter (DN)	Thread Type	Weight (kg)
PG 10651 P	3	12.5	280	250	Tr	47.430
PG 10652 P	4	12.5	280	250	Tr	62.730
PG 10715 P	1	16	280	250	Tr	21.230
PG 10716 P	2	16	280	250	Tr	40.530
PG 10717 P	3	16	280	250	Tr	59.830
PG 10718 P	4	16	280	250	Tr	79.130
PG 10781 P	1	14.5	330	300	Tr	23.045
PG 10782 P	2	14.5	330	300	Tr	43.995
PG 10783 P	3	14.5	330	300	Tr	64.997
PG 10784 P	4	14.5	330	300	Tr	85.895
PG 11243 P	1	19	330	300	Tr	29.700
PG 11244 P	2	19	330	300	Tr	56.700
PG 11245 P	3	19	330	300	Tr	83.700
PG 11246 P	4	19	330	300	Tr	110.700
PG 10847 P	1	17.5	400	350	Tr	33.600
PG 10848 P	2	17.5	400	350	Tr	64.260
PG 10849 P	3	17.5	400	350	Tr	94.860
PG 10850 P	4	17.5	400	350	Tr	125.460
PG 10913 P	1	21.5	400	350	Tr	41.250
PG 10914 P	2	21.5	400	350	Tr	78.750
PG 10915 P	3	21.5	400	350	Tr	116.250
PG 10916 P	4	21.5	400	350	Tr	153.750
PG 10979 P	1	19.5	450	400	Tr	42.350

Code No	Length (L)	Thickness (s)	Outside Diameter (d)	Nominal Diameter (DN)	Thread Type	Weight (kg)
PG 10980 P	2	19.5	450	400	Tr	80.850
PG 10981 P	3	19.5	450	400	Tr	119.350
PG 10982 P	4	19.5	450	400	Tr	157.850
PG 11045 P	1	23.5	450	400	Tr	50.600
PG 11046 P	2	23.5	450	400	Tr	96.600
PG 11047 P	3	23.5	450	400	Tr	142.600
PG 11048 P	4	23.5	450	400	Tr	188.600